

PTZ IP Dome Camera

H.265 (3MP PTZ IP Camera)



Function Features

- IP Dome PTZ 3.0 Megapixel
- ONVIF Supports
- Lens: 4.7MM~90MM
- 30X optical zoom
- Electric Shutter: PAL : 1/25~100000s NTSC : 1/30~1/100000s
- H.264 Main Video Comparison
- 100 Meters IR Distance
- Support POE

SPECIFICATIONS

PTZ IP Dome Camera	
Model No	AE-4IP3PTZ30
Image Sensor	1/3" CMOS
Resolution	3.0MP (2048*1536)
Effective Pixel	2048x1536
Signal Model	PAL / NTSC
Focus Length	4.7mm~90mm
Zoom	30X Optical Zoom
Min. Illumination	Color:0.1Lux B/W : 0.01Lux, Color to B/W
Backlight compensation	On/Off
S / N Ratio	≥60dB (Enhanced)
White Balance	Auto
Focus	Auto/Manual/Push Auto
IR Distance	100 Meter
Patrol Track	1 Groups, Can Record for 3Mins
Cruise Track	1 Groups, Can add 16 presets
Other Scan	Support Horizontal Scan, Deuce area scan, Scan Random
Rotation Range	Horizontal 360° unlimited Rotation, vertical 90°, auto reversal
Horizontal Range	360° Continuous Rotation
Rotation Speed	Horizontal and vertical Min 0.01°, Max 35°/s
POE	Supports
Electric Shutter	PAL : 1/25~100000s NTSC : 1/30~1/100000s
Preset Call Speed	Max 35°/S
Manual Call Speed	0.01°~35°/s
Presets	255
Video Compression	H.264 Main Profile Encoding ; MJPEG / JPEG Baseline Encoding
Audio Compression	G.711, G.726
Primary Stream	2048*1536 25fps
Secondary Stream	VGA, QVGA,
Video Bit Rate	32Kbps-16Mbps Continiously Adjustable, Support CBR / VBR
Network Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE,
ONVIF Support	Support
Power Supply	DC12V 3A
Work Environment	-20°C~+50°C (Select temprature control accessories), <95%RH