

PTZ IP Dome Camera

H.265 (3MP PTZ IP Camera)



Function Features

- IP Dome PTZ 3.0 Megapixel
- ONVIF - 2.4
- Lens: 4.7MM~90MM
- 30X optical zoom
- Electric Shutter: PAL : 1/25~100000s NTSC : 1/30~1/100000s
- IR Range 150 Meters
- IP66 rate protection
- Support POE
- H.264 Main Video Comparison

SPECIFICATIONS

PTZ IP Dome Camera	
Model No	AE-6IP3PTZ30
Image Sensor	1/3" CMOS
Resolution	3.0MP (2048x1536)
Effective Pixel	2048x1536
Video Compression	H.264
Focus Length	F=4.7mm~90mm
Zoom	30X Optical Zoom
Min. Illumination	Color:0.1Lux B/W : 0.01Lux
Backlight compensation	On/Off
S / N Ratio	≥60dB
White Balance	Auto
IR Light Control	Intelligent Control Technology
IR Range (Night)	150 Meter
IR On	Auto/Manual/Auto/Timing
IR Angle	Infrared Zoom Matching Technology
IR Light Power	Manual Settings
IR Life	30000 Hours
Horizontal Range	360° Continuous Rotation
Tilt Rotation Speed	-90° ~ 0°
POE	Supports
Electric Shutter	PAL : 1/25~100000s NTSC : 1/30~1/100000s
Preset Call Speed	Max 35°/S
Manual Call Speed	0.01°~35°/s
Presets	255
Cruise Track	1 Groups, groups for 16 Presets
Video Compression	H.264 Main Profile Encoding ; MJPEG / JPEG Baseline Encoding
Audio Compression	G.711, G.726
Primary Stream	2048*1536 25fps
Secondary Stream	VGA, QVGA, 25fps
Video Bit Rate	32Kbps-16Mbps Continuously Adjustable, Support CBR / VBR
Network Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE,
ONVIF Support	Support
Cooling Structure	Dustproof Structure Outside The Circle
Protection Level	IP66
Power Supply	DC12V 3A
Power	35W
Work Temperature	-35-65°