


Smart NVR

H.265 (128CH 4K NVR)



FUNCTION FEATURES

- Support 128CH 4K IP Camera Input.
- Support IPC centralized management, including IPC parameter configuration, information export and import, real-time information acquisition and upgrade, etc.
- Support our Smart IPC: Humanoid Detection, Retrograde Detection, Leave Position Detection.
- Support synchronous recording, remote monitoring, backup.
- Support preview image and playback image 12 times electronic magnification.
- Standard ONVIF, SLINK, RTSP protocol.
- Support DDNS, EMAIL, UPNP, P2P and other functions.
- Support WEB, mobile phone monitoring, VMS monitoring.
- Supports disk grouping quotas and disk group storage modes.
- Support channel grouping, preview tour.
- Supports maximum 4CH sub-stream recording synchronous playback and multi-channel synchronous playback, capture playback.
- Support double password authentication.
- Support network monitoring: network traffic, network delay packet loss test, network packet capture backup.
- Support current bandwidth, stream information.
- Support multiple language, micro-intelligence, capture playback.

SPECIFICATIONS

NVR													
Model No													AE-PR-128NVR-4K-S9/S16
Main Chipset													Hi3536
Operating System													Embedded Linux
Bandwidth													640m
Video Format													H.265+/H.265/H.264
Video Resolution													4K/5MP/3MP/1080P/720P/D1
Smart Functions													Humanoid Detection, Retrograde Detection, Leave Position Detection
Record Mode													Timing and Alarm Recording, Timing Recording, Alarm Recording, Stop recording, Motion Detection Recording
Playback													1CH 4K/4CH 4K/9*3MP/16CH 1080P
Backup Mode													USB Device/Network
Video													
16CH Comparison mode		16CH comparison IPC+112CH normal IPC											
		Split	1	4	6	8		9	16	25	36	64	128
		Decode	4K	4K	4K+5*2MP	4K+7*2MP	2MP	1080P	720P	D1	D1	D1	
Normal Mode		64CH normal IPC											
		Split	1	4	6	8		9	16	25	36	64	
		Decode	4K	4K	4K+5*2MP	4K+7*2MP	2MP	1080P	720P	D1	D1	D1	
Normal Mode		128CH normal IPC											
		Split	1	4	6	8		9	16	25	36	64	128
		Decode	4K	4K	4K+5*2MP	4K+7*2MP	2MP	1080P	720P	D1	D1	D1	
Video/Audio/Alarm													
Video Input		128CH Digital (4000X3000) + 64CH Preview + 16CH Playback + Face Recognition 64CH Digital (4000X3000) + 64CH Preview + 16CH Playback 128CH Digital (4000X3000) + 64CH Preview + 16CH Playback Support import 5000 face database											
Video Output		2 HDMI, 2 VGA											
Audio Input & Output		HDMI audio											
Alarm Input & Output		N/A											
Port													
HDD		9 SATA/16 SATA, Each port supports MAX 8TB HDD											
E-Sata		N/A											
Network													
Network Interface		2*RJ45 10M/100M/1000M self-adaptive LAN port											
Network Function		DDNS, EMAIL, UPNP, NTP, DHCP, IP Filter, PPPoE, P2P											
Smart Phone		iPhone, Android											
External Ports													
USB		3 USB Ports(2USB2.0/1USB3.0)											
RS232		N/A											
RS485		N/A											
Others													
Power Supply		9 SATA - AC100-240V,200W 16 SATA - ATX110-220V,300W, 50-60Hz											
Power Consumption		≤50W(without HDD)											